



AMS FF14 FRICTION FEEDER



Improves the efficiency and presentation of your packaging processes

What Does It Do?

The AMS FF14 friction feeder has been designed to be used with the AMS range of envelope addressing printers as well as tabbers, mail inserters, polywrapping machines and other mail insertion equipment. The well built steel construction includes 16-rollers and can stand up to the most demanding production environment. The performance, reliability and flexibility make the feeder an important cost-saving tool for any production application.

Easy To Use

The AMS FF14 can easily feed a range of stock, card and paper up to 10mm in thickness. Friction feeders have long had a reputation of being the speediest type of feeders, and the AMS FF14 is no exception. Easily able to feed 40,000 mailing pieces per hour, the feeder can be controlled to speed up or slow down output. It has a double clutch and break-feed system for precise starting and stopping and it uses fibre-optic sensor and microprocessor for reliable and accurate feeding.

The feeders powerful motor makes it strong enough to feed the most demanding application, it also requires little maintenance as the sealed roller bearings do not require oiling or cleaning. It has the reliability to provide years of uninterrupted service.

Key Features:

Feeds at speeds up to 40,000 per hour

Strong - Built to Last Feeder

Includes Auto Host Wait Detection System

Easily Adapted For Various Materials, Cards and Papers

Logic Operating Feed Rollers

Easy Load Feed Mechanism

Solid Steel Construction

Ready to Hook Up To Host For Intelligent Feeding

Installed In-Line, On-Line and Off Line

OPTIONAL EXTRAS

Optional Equipment

AMS manufacture a range of machine cabinets that will easily support your mailing equipment as well as provide ample storage space. AMS also manufacture a range of conveyor stackers and dryers to complement your equipment thereby making it easier and more efficient to produce your mailings.

Supplies

AMS supply a wide range of low-cost consumables to suit our mailing equipment including inkjet cartridges and envelopes.

SPECIFICATIONS

Speed:	Up to 40,000 per hour. Speeds are dependent on application
Material Sizes	Min: 51mm x 76.2mm - Max: Subject to test
Material Thickness	Up to 10mm
Operation	Auto By Host, One Shot & Continuous
Counters	One Resettable
Feeder Capacity	Up to 750 DL Envelopes
Interface	Loop Controllable By Host

TECHNICAL INFORMATION

Machine Dimensions	(W)381mm x (L)483mm x (H) 432mm
Weight	22.7kg
Electrical	230vAC 50/60Hz

Why Choose An AMS Feeder?

AMS is one of the UK's leading suppliers of mailroom equipment. As well as having a dedicated team of knowledgeable experts to offer advice and bespoke solutions to suit your mailing needs, we have a well-trained customer support team and highly skilled team of field engineers to support you after your purchase.

This reliable and efficient after-care support service is provided to ensure you get the most out of your purchase. We also offer a comprehensive range of technical support and service packages that cover both equipment and software.