

Tel: 01992 460 111 Email: sales@ams-gb.com Web: www.amsmailingsystems.co.uk

#### **AMS L1 COLOUR LABEL PRINTER**



#### What is it?

The L1 Colour label printer represents a groundbreaking advancement in Memjet inkjet technology, setting new standards for performance, versatility, and user-friendly operation. With its reconfigured print engine, the L1 ensures a seamless printing experience by providing a flat and unobstructed printing path, guaranteeing consistently crisp and immaculate results with every print job. The flat media path accommodates input rolls of any diameter, offering unparalleled convenience and flexibility when working with various media sizes.

The L1 label printer excels in adaptability, thanks to its adjustable media sensors, allowing you to effortlessly print on a diverse range of label shapes, perfectly tailored to meet your specific labeling requirements. Impressively, the L1 printer achieves a remarkable print quality of  $1600 \times 1600$  dpi, enabling the production of stunning full-color graphics that captivate the eye.

## Why do you need it?

The L1 Label printer allows you to have complete control of your label production. Lower costs, efficiency, and reliability are just a few of the benefits of the L1 printer. The intuitive interface and user friendly 7" touchscreen streamlines printer operation to produce stunning graphics for your business.

### **Key Features:**

- Operator friendly 7" touchscreen display:
  - -Monitor printer status, ink levels, job status and more at a glance
  - -Touchscreen buttons control often-used printer functions
- Prints from any diameter label roll
- Onboard data storage to effectively store job history
- Economical. Very low cost-per-copy



# **Specifications**

_	
Print Cartridge	Memjet® Replaceable Printhead
Speed	High Quality Mode: 6" (15cm/sec) Normal Quality Mode: 12" (30cm /sec)
Print Quality (DPI)	Best: 1600 x 1600 DPI Normal: 1600 x 800 DPI
Image Area	8.5" (215.9 mm) x Continuous Length
Media Types	Roll or Fanfold (Label, Tag)
Media Thickness	Minimum: 3 points (0.1 mm) Maximum: 12 points (0.3 mm)
Minimum Label Gap (space between labels)	3 mm. Stiching option available in printer toolbox
Media Sensing	Label gap, notch, tick mark (continuous, blackmark, diecut
Ink	Water-based ink. Five 250ml Ink resevoirs (CMYKK)
Ink Monitor	Viewable on 7"Touchscreen Display and L-Series toolbox
Software	WindowsTM Printer Drivers for WindowsTM; 8, 8.1,10. RIP available
Diagnostics	Viewable on 7"Touchscreen Display and L-Series toolbox
Data Storage	Onboard Printer storage for Job Library
Firmware Update	Flash update through L-Series Toolbox
Network Interface	Ethernet Port
Equipment Interface	DB-9 Connector to interface printer with other equipment
Counters	Permanent lifetime and job counter is viewable on 7" Touchscreen Display and L -Series Toolbox
Dimensions	20 - 1/4" W x 22-1/2" L x 13-1/2" H (51.4cm x 56.5cm x 34.3 cm)
Weight	75lbs. (34kg)
Electrical	50/60 Hz







**Optional Equipment:** AMS manufacture a range of machine cabinets that will easily supportyour mailing equipment as well as provide ample storage space. AMS also manufacture a range of conveyor stackers to complement your equipment, thereby making it easier and more efficient to produce your mailings.

**Mailing Supplies:** AMS supply a wide range of low-cost consumables to suit our mailing equipment including labels, inkjet cartridges and envelopes.

#### **Why Choose An AMS Label Printer?**

AMS is one of the UK's leading suppliers of mailing and packaging equipment. As well as having a dedicated team of knowledgeable experts to offer advice and bespoke solutions to suit your mailing needs, we have a well-trained customer support team and highly skilled team offield engineers to support you after your purchase.