

AMS MERCURY S2 ENVELOPE SEALING SYSTEM



Improves the efficiency and presentation of your mailing processes

What Does It Do?

The envelope sealing system can quickly seal your envelopes and comes with an optional automatic stop/start function and optional counter. The unique system can seal up to 300 envelopes per minute, that's around 18,000 per hour! Users are even able to adjust the output speed if needed.

Gummed envelopes of various lengths up to 380mm can be sealed and up to 15mm in thickness. As the machine has low noise levels, it is suited to office environments.

Easy To Use

The simple system can work automatically and requires only the loading up of the prepared envelopes. The auto-start/stop option for stacked envelopes means it will stop when the envelopes have run out and only restart when it is re-loaded. There is also an option to integrate a counter.

There is no need to open the envelope flaps manually or hold or press on the piles of letters. The adjustable sealer has a large visible water reservoir so you can see when it needs to be refilled and a self-cleaning moistening roller eliminates the need for maintenance.

Key Features:

Up to 18,000 gummed envelopes can be sealed per hour

Fully automated start/stop system (optional)

Seals envelopes effectively and quickly to 335mm wide

Integrated counter (optional)

Large water reservoir

Adjustable moistening intensity

Speed regulation provides selectively adjustable output

Simple to operate

Great build quality

OPTIONAL EXTRAS

With this machine you are able to seal and count envelopes simultaneously. The machine with integrated counter can be used as a sealer and/or counter. Thanks to its deeper design this new series "MERCURY S2" is particularly suited for all common standard envelopes with the formats C5, C6/5, C4, B4 and C4 pocket (324x229mm) with the flap on the short side.

Supplies

AMS supply a wide range of low-cost consumables to suit our mailing equipment including inkjet cartridges and envelopes.

SPECIFICATIONS

| | |
|--|-------------------------------------|
| Max. sealing capacity (C5, C5/6): | 18,000 envelopes per hour |
| Max. width of envelope: | 335 mm (B5/B4, C6/5, C4, C4 Pocket) |
| Max. length of envelope: | 380 mm |
| Max. thickness of envelope: | 15 mm |
| Operating voltage: | 85VAC...264VAC / 50...60Hz, 1.6A |
| Automatic feeding: | yes |
| Piling-Option (for stacked and nested envelopes!): | yes |
| Automatic Start/Stop: | optional (model MERCURY S2-IR/IRC) |
| Counter (integrated): | optional (model MERCURY S2-C/IRC) |
| Batch-Counter (integrated): | optional (model MERCURY S2-IRBC) |

QUALITY AND SAFETY

| | |
|--------------|--|
| Display: | yes (model with counter) |
| Signal lamp: | LED |
| Area of use: | according to EU-Norms |
| Licensing: | CE |
| Warranty: | 2 years |
| Accessories: | Line cable (2m), cover, suction rubber pear, re-placement fuse, instruction manual |

DIMENSIONS

| | |
|---------------------------------|------------------------------------|
| Dimension incl. receiving tray: | 1110 (max.) x 365 x 450 mm (lxhxw) |
| Length of receiving tray: | 400 mm |
| Weight incl. receiving tray: | 32.1kg |

Why Choose An AMS Envelope Sealer?

AMS is one of the UK's leading suppliers of mailroom equipment. As well as having a dedicated team of knowledgeable experts to offer advice and bespoke solutions to suit your mailing needs, we have a well-trained customer support team and highly skilled team of field engineers to support you after your purchase.

This reliable and efficient after-care support service is provided to ensure you get the most out of your purchase. We also offer a comprehensive range of technical support and service packages that cover both equipment and software.