AMS Mailing Systems, Unit 21 Mead Park Industrial Estate River Way, Harlow, Essex, CM20 2SE

Tel: 01992 460 111

Email: info@amsmailingsystems.co.uk Web: www.amsmailingsystems.co.uk



WRAPMATIC L-SEALER SYSTEM COMPARISON

WrapMatic Compact Features:

- Automatic fully electric L-sealer system with built in shrink tunnel
- Optional come back conveyor ideal for one operator
- Max product size mm: 420(I) x 400(w) x 120(h)
- Up to 1200 hourly output (depends on the product, film and operator)
- Simple and functional design
- Extremely compact



WrapMatic 160 Features:

- Automatic fully electric L-sealer system
- Max product size mm: 600(l) x 400(w) x 160(h)
- Up to 2800 hourly output (depends on the product, film and operator)
- Simple and functional design
- Front and rear opening for easy access
- Shrink tunnel optional



WrapMatic 240 Features:

- Automatic fully electric L-sealer system
- Max product size mm: 600(I) x 400(w) x 240(h)
- Up to 3600 hourly output (depends on the product, film and operator)
- Simple and functional design
- Front and rear opening for easy access
- · Shrink tunnel optional
- Side seal version available
- FDA approved stainless steel option



WrapMatic 360 Features:

- Automatic fully electric side sealer system
- Max product size mm: unlimited(I) x 400(w) x 360(h)
- Up to 2400 hourly output (depends on the product, film and operator)
- Simple and functional design
- Front and rear opening for easy access
- Shrink tunnel optional
- FDA approved stainless steel option

